



51 x 16 x 8 mm



Technical Data

Bluetooth v2.1 + EDR, Data rate: up to 3 Mbps
 Bluetooth Class 1: 100 meters, Class 2: 20 meters
 Chipset: CSR/ISSC/Broadcom
 Spread spectrum: FHSS
 Connect up to 7 different enable Bluetooth devices
 LED indicator: single LEDs
 Sensitivity: < 0.1% BER at -80 dBm
 Powered: 5 Volt via USB
 RF output power: 13 dBm
 Modulation method: GFSK, TT/4-DQPSK, 8-DPSK
 Systems supported: Windows 98SE, 2000, XP, Vista, 7
 Bundled Bluetooth software: licensed BlueSoleil/Widcomm
 Certificates: CE, RoHS

Supported Bluetooth profiles:
 A2DP (Advanced Audio Distribution)
 AVRCP (Audio Video Remote Control)
 BIP (Basic Imaging Profile)
 OPP (Object Push Profile), FTP (File Transfer Profile)
 BPP (Basic Printing Profile), FAX (Fax Profile)
 HID (Human Interface Device Profile)
 DUN (Dial-up Networking Profile)
 PAN (Personal Area Networking Profile)
 LAP (LAN Access Profile)
 HFP (Hands Free Profile), HSP (Headset Profile)
 HCRP (Hardcopy Cable Replacement Profile)

Application Show



Package Details

